

AUSTRALIAN SCAFFOLD

WORK SAFER - FASTER - SMARTER

(02) 9627 1700

"Give us a call, you'll be glad you did"

**1300 MD SERIES—S.W.L 450 KGS (2.6mm wall thickness)
1.3M WIDE X 2.5M LONG X 3.0M HIGH**



CODE	COMPONENTS	QTY
MBD2500	2.5M Plan brace	1
MBD2500	2.5M Diagonal brace	8
MBH2500	2.5M Horizontal brace	8
MPT2500	2.5M X .54M Hatch deck	1
MPS2500	2.5M X .54M Plain deck	1
MWA8000	8" Adjustable castors	4
MLAD4000	4.0M Ladder & brace	1
MFR1305	2.0M End frame	4
LTOE2513	Toe board set	1

FEATURES

- * 50.8mm tube.
- * Guaranteed for life.
- * Adjustable wheels & brakes.
- * Components are fully TIG welded.
- * Extruded & manufactured for T6-6061 alloy.
- * 5 Times lighter than similar steel scaffold components.
- * Chemically tested and certified to Australian Standards.

Supplied with test certificates and instructions of use.



Australian Scaffolds Pty Ltd A.B.N 66 124 410 359

71 Hobart St, Riverstone NSW 2765 Phone: 02 9627 1700 Fax: 02 9627 1701

Web: www.australianscaffolds.com.au Email: info@australianscaffolds.com.au